





- Patented Reinforced Mineral Wool Core Benefits
- Superior low frequency and overall absorption " Class A fire protection (Flame Spread:10, Smoke Developed Rating:95)
- Durable cores that will last in gymnasiums or high-impact environments
- Tensile strength minimum of 2,631 lbs./sq.ft breaking load
- Compressive resistance of 547 psf at 25% compression
- Contribute to LEED ®credits
- Made using natural inorganic materials with at least 75% recycled content
- 6-8 lb. density
- Melting point of 2,150°F(ASTM E-136)
- Water repellent - will not mold, rot, or corrode

- Ideal for the walls in offices, conference rooms, and classrooms, the Flat Panel can also be used to add absorption to a ceiling surface
- Unmatched Class A fire protection as a complete panel assembly
- Customized with a square or beveled edge
- Perfect product to help negate echo



	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC	Overall Vs Fiberglass	Frequency Absorption
1"	.28	.67	1.11	1.05	.98	.98	.95	+18%	180%

Dimensions	2'x2' to 4'x8'; Custom sizes available
Panel Depth	1"
Fabric	Selected from our manufacturer's standard fabric
Core Material	Rockwool
Backing	Fiberglass Mat
Edge Treatment	Regular edge
LEED Eligible	Yes