


PANEL TECH SPECS



FLAT PANEL




WAVE™



WEDGE
Wedge™



MEGA WEDGE™



MAX WEDGE™

FLAT PANEL

Ideal for the walls in offices, conference rooms, and classrooms, the Flat Panel can also be used to add absorption to a ceiling surface.

- Industry leader in sound absorption with a 33% increase in overall absorption over 2" Fiberglass Panels
- Unmatched Class A fire protection as a complete panel assembly
- Customized with a square, bevel, or radius edge
- Regular or PVC-hardened edge finish
- Perfect product to help negate echo (2" spec)

125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
.31	1.05	1.67	1.50	1.37	1.30	1.40*

*Spaced Arrangement

Also available in 1", 3" and 4"

WAVE

The Wave™/EconoWave™ Diffusers** provide an aesthetic option in youth rooms, video conference rooms, cafes, and gymnasiums

- 72% increase in low frequency absorption over 2" Fiberglass Panels
- 52% increase in overall absorption over 2" Fiberglass Panels
- Unmatched Class A fire protection as a complete panel assembly
- Waves from 1" to 3" across the width of the panel

125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
.50	1.10	1.72	1.86	1.63	1.48	1.60*

**Wave™ Diffusers available in 2' widths and EconoWave™ Diffusers available in 4' widths

*Spaced Arrangement



• Slope from 1 3/16" to 3 3/16" across the 2' width of the panel

• Slope from 1 3/16" to 3 3/16" across the 4' width of the panel

- 72% increase in low frequency absorption over 2" Fiberglass Panels
- 52% increase in overall absorption over 2" Fiberglass Panels

125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
.50	1.10	1.72	1.86	1.63	1.48	1.60*

MegaWedge™

EconoMegaWedge™

• Slope from 3 3/16" to 5 3/16" across the 2' width of the panel

• Slope from 3 3/16" to 5 3/16" across the 4' width of the panel

- 390% increase in low frequency absorption over 2" Fiberglass Panels
- 86% increase in overall absorption over 2" Fiberglass Panels

125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
1.42	1.61	2.19	2.13	1.89	1.75	1.95*

MaxWedge™

EconoMaxWedge™

• Slope from 1" to 7" across the 2' width of the panel

• Slope from 1" to 7" across the 4' width of the panel

- 341% increase in low frequency absorption over 2" Fiberglass Panels
- 110% increase in overall absorption over 2" Fiberglass Panels

125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	NRC
1.28	1.71	2.51	2.40	2.08	1.90	2.20*

*Spaced Arrangement